

Engineering Submittal Form - MX-12SA14

CERTIFIED FOR:

· · · · · · · · · · · · · · · · · · ·	
Job Name:	Customer Name:
Location:	Customer P.O.:

Recommended Usage:

Use as a free standing; non-penetrating pipe support stand for all piping applications installed on single ply and built-up roofs within the recommended weight limit. This support is designed to accommodate single or multiple runs of conduit. (Specific consideration should be given to the size of conduit and the recommended weight limits.) Additionally, this support may be utilized for securing refrigeration line sets or natural gas piping when thermal expansion is not a concern. The adjustable rod assembly allows piping to be installed level on tapered roofs. The addition of the optional neoprene pad adhered to the base provides additional protection for the roof during installation. All supports are available with optional MWP Series- ½" Walk Pad and adhesive for "in the field" application.

Standard Composition:

Support Base is 18 gauge - 304 stainless steel with all stainless steel hardware and features rolled edges to prevent incidental damage to roof surface. All with stainless steel hardware: The aluminum strut provides the means for securing several pipes.



MAPA Products Supports are designed and manufactured in accordance with MSS SP-58-2002 and MSS SP-69-2002.

Refer to MAPA Products "Recommended Installation Guidelines" for standard installation and spacing recommendations.

Composition:

Strut Assembly 12" – 1 5/8" Aluminum Shallow Strut Threaded Rod Assembly 1/2" X 14" Grade 304 SS ATR

Maximum Adjustability
Base Dimensions
Footprint
Weight Limit

4" – 14"
6" X 12"
72 sq in.
195 lbs

* When used for conduit; specific consideration should be given to the size and number of conduits and the supports recommended weight limit so that maximum support load is not exceeded.

Optional Accessories:

MWP1016- ½" thick rubber walk pad

Snap-N-Strut Clamps (Refer to SNS selection chart for sizing)

Warranty

ISIMET / MAPA, LLC will repair or replace any defective parts or workmanship of this product for a period of three years from date of delivery. Rusting that is not detrimental to the integrity of the support is not warranted. Damage caused by incorrect installation, alteration or improper usage is not warranted. Recovery rights shall be limited to the total sum of the amounts paid for the product by the purchaser.

Limits of Liability:

ISIMET / MAPA, **LLC** liability shall be limited to costs of repair or replacement parts. Supports are not intended for usage other than those expressly described in this brochure. **ISIMET / MAPA**, **LLC** shall not be liable for damage or injury caused by the improper use of the product.

	tion Data Suppo Opt	ort Pad ions							
QTY	NP	WP	Pipe Size	Service	SNS Select	on	Note	es & Options	
DRAWN			CHECKED	CHECKED		DATE		DWG.NO.	

Doc. #: M-13819